

# DEVELON

## Wheel Loader

# DL250TC-7



### Engine

Make	DEVELON
Model	DL06P
Number of cylinders	6
Rated power, gross (hp per SAE J1995)	171.7 hp (128 kW) @ 2100 rpm
Rated power, net (hp per SAE J1349)	171.7 hp (128 kW) @ 2100 rpm
Max. torque, net (SAE J1995)	593 lbf.ft. (804 Nm) @ 1400 rpm
Displacement	360 in. <sup>3</sup> (5.9 L)
Bore and stroke	3.94 in. x 4.92 in. (100 mm x 125 mm)
Starter	24 V, 8.6 hp (6.0 kW)
Battery (qty 2)	24 V, 100 AH, 900 CCA
Alternator	24 V, 80 amp
Air cleaner	Dry, double elements

### Hydraulics

Main pumps	Variable Displacement Axial Piston Pump 48.8 gpm (184.8 L/min.)
System pressure (work)	3843 psi (265 bar)
System pressure (steer)	2828 psi (195 bar)
Boom speed – up	5.7 +/- 0.5 sec
Boom speed – down	3.7 +/- 0.3 sec
Bucket speed – crowd	1.7 +/- 0.3 sec
Bucket speed – dump	2.6 +/- 0.2 sec

### Travel Speeds

Travel speed – forward (4)	4.1 / 7.2 / 14.1 / 23.5 mph (6.4 / 11.7 / 22.7 / 37.2 km/h)
Travel speed – reverse (3)	4.1 / 7.7 / 14.7 mph (6.7 / 12.4 / 23.8 km/h)
Max. grade	58% (30°)

### Environment

Sound level (ISO 6395)	104 dB(A)
Cabin sound level (ISO 6396)	70 dB(A)

### Refill Capacities

Fuel tank	62.08 gal. (235 L)
DEF tank	8.32 gal. (30 L)
Cooling system (radiator capacity)	8.29 gal. (31.4 L)
Engine oil	6.5 gal. (24.5 L)
Transmission	8.45 gal. (32 L)
Front axle	9.25 gal. (35 L)
Rear axles	6.7 gal. (23 L)
Hydraulic system	39.63 gal. (150 L)

### Hydraulic Cylinders

Steering (2) bore x rod diameter x stroke	3 in. x 2 in. x 17 in. (70 mm x 45 mm x 425 mm)
Lift arm (2) bore x rod diameter x stroke	5 in. x 3 in. x 31 in. (120 mm x 75 mm x 790 mm)
Bucket (1) bore x rod diameter x stroke	4 in. x 3 in. x 35 in. (105 mm x 65 mm x 881 mm)


The piston rods and cylinder bodies are made of high-strength steel. A shock-absorbing mechanism is fitted in at the base and rod end of the lift and bucket cylinders and the rod end of the steering cylinders to ensure shock-free operation and extended piston life.

# Dimensions

## Standard Arm

Bucket capacity, heaped ISO/SAE		3.1 yd <sup>3</sup> (2.4 m <sup>3</sup> )
Overall length	A	25' 7" (9219 mm)
Bucket width	B	8' 11" (2740 mm)
Overall height, ROPS cabin	C	10' 9" (3280 mm)
Width at tires	D	8' 5" (2570 mm)
Wheel base	E	9' 10" (3050 mm)
Tread width	F	6' 8" (2040 mm)
Ground clearance	G	1' 5" (431.8 mm)
Dump height (45°) – fully raised	H	9' 0" (2750 mm)
Dump reach (45°) – fully raised	I	4' 3" (1299 mm)
Max. hinge pin height	J	12' 10" (3934 mm)
Max. tilt angle on ground	K	42°
Max. dump angle at fully raised	L	50°
Max. tilt angle at fully raised	M	51°
Max. tilt angle at carry position		48°
Max. steering angle		40°
Digging depth		3" (132 mm)
External turning radius, bucket edge		20' 2" (6150 mm)
External turning radius, outside tire		18' 1" (5508 mm)
Tire size		20.5R25 L3
Operating weight		31605 lb. (14336 kg)
Static tipping load (straight)		20470 lb. (9285 kg)
Static tipping load (at full turn)		18078 lb. (8200 kg)
Breakout force		22930 lbf. (101999 N)

Front Lift Arm Configuration  
Standard: US10



# Standard & Optional Equipment

| Standard Base Package, US10

■ Standard ● Optional – N/A

## Engine

Emissions, T4 (EPA)	■
High-pressure common-rail (HPCR)	■
Cooled exhaust gas recirculation (CEGR)	■
Diesel oxidation catalyst (DOC)	■
Selective catalyst reduction (SCR)	■
Diesel exhaust fluid (DEF)	–
Diesel particulate filter (DPF)	–
Fuel filter with water separator	■
Coolant recovery tank	■
Dual element dry-type air filter with evacuator	■
Pre-cleaner	■
Electronic engine control (ECU)	■
Auto idle (working to standby)	■
Auto shutdown (time adjustable)	■
Overheat & low oil pressure engine protection	■
Cooling fan – radiator, variable speed	■
Cooling fan – radiator, automatic reversible	■
Remote drain port – engine oil	■
Block heater (110 V)	●

## Hydraulic

Variable displacement axial piston pump	■
Closed-center system	■
Main control valves, pilot	■
Remote test ports	■
Remote drain port, hydraulic oil	■
Parking brake, spring-applied hydraulic release	■
Auxiliary hydraulics (3rd valve)	■
Automatic boom/lift kick-out, adjustable (in cab)	■
Automatic return-to-dig position, adjustable	■
Boom float	■
Load isolation system	●

## Electrical

System voltage – 24 V	■
Alternator – 24 V, 80 amp	■
2 x 12 V batteries, 100 AH reserve capacity, 900 CCA	■
Blade-type fuse panel	■
Main circuit breaker	■
Lights, work (LED): front (2), rear (2)	■
Lights, work (LED): front (4), rear (4)	●
Lights, work (LED): front (6), rear (6)	●
Lights, headlights (halogen) – hi/lo beams (2)	■
Lights, stop, tail & direction indicators	■
Horn	■
Rotating beacon	●
Hour meter	■
Engine restart prevention system	■
Rearview camera	■
Laptop service port	■
Self-diagnostics system	■

## Cabin

Steel, all-weather & sound-suppressed	■
ROPS (ISO 3471)	■
FOPS (ISO 3449, level II)	■
Front window with wiper/washer	■
Rear window with wiper	■
Tinted safety glass	■
Visor, retractable	■
Adjustable sliding side door window	■
Defrost, front window	■
Lockable doors	■
Seat	■
- Air suspension	■
- 2" (51 mm) seat belt	■
- Adjustable height & recline	■
- Adjustable fore/aft	■
- Adjustable armrests	■
Control stands	■
- Height adjustable	■
- Fore/aft adjustable	■
Storage for operator's manuals	■
Mirror, interior rearview (1)	■
Mirror, exterior (2), heated	■
Mirror, exterior (2), heated (electronic adjustable)	●
Fully automatic HVAC with ambient temperature sensor	■
Smart Touch display	■
- 8" touch-enabled	■
- Adjustable height & angle	■
Transparent bucket	■
- Multi-camera system & controller	■
- In-cab display	■
AM/FM stereo with hands-free Bluetooth®	■
Speakers (2)	■
Antenna, roof-mounted	■
Emergency breakout tool	■
Hot/cold beverage compartment	■
360° all-around view camera with backup sensor	●
Power socket, 12 V	■
Power socket, USB	■
Cup holder	■
Interior light	■
Coat hanger	■

## Controls

Adjustable steering column	■
- Tilting	■
- Telescoping	■
Emergency secondary steering	●
Throttle pedal (accelerator)	■
Brake pedal, right	■
Brake pedal, left	■
Intelligent clutch cut-off	■
Gear selector (FNR)	■
Joystick control	■
Switches, console-mounted	■
- Starter (button)	■
- Parking brake	■
- Pilot cutoff	■
- Transmission cutoff	■
- Work light	■
- Reversible cooling fan	■
Emergency stop switch	■
Power mode (P, S, E)	■
Transmission mode	■
Wiper control panel	■
Audio control panel	■

## Display Monitor & Warnings

Buzzer	■
- Engine oil pressure	■
- Coolant temperature	■
- Transmission overheat	■
Gauges	■
- Fuel level	■
- DEF level	■
- Engine coolant temperature	■
- Transmission oil temperature	■
- Engine rpm	■
- Speedometer	■
- Transmission gear indicator	■
- Battery voltage	■
- ECO	■
- Smart guidance system	■
- Digital clock	■
- Trip meter	■
- Hour meter	■
- Total operation time	■
- Fuel consumption	■
Warning & indicator lights	■
- Seat belt	■
- Error code	■
- SCR warning	■
- Check engine	■
- Engine oil pressure	■
- Engine pre-heat engaged	■
- Radiator coolant level	■
& temperature	■
- Air filter	■
- Fuel level	■
- DEF level – low	■
- Water in fuel	■
- Battery charge	■
- Direction signal	■
- Lights (high, main, work, beacon)	■
- Emergency steering	■
- Hydraulic oil temperature	■
- Hydraulic charge	■
pressure warning	■
- Hydraulic pilot filter	■
- Hydraulic return filter	■
- Transmission mode	■
- Transmission warning	■
- Transmission lock-up	■
- Transmission oil temp	■
- Transmission gear indicator	■
- Brake fluid pressure warning	■
- Reverse fan indicator	■
- Mirror heat indicator	■
- Parking brake indicator	■
Back-up alarm	■
Scale system, integrated smart scale	●
Around view monitor (AVM)	●

## Frame & Driveline

Z-bar lift arm	–
Parallel lift	■
Steering cylinder, double-acting (2)	■
Transmission – 4F/3R speed	■
- Full automatic power shift	■
- Torque converter	■
Differentials	■
- Limited slip front/rear	■
Hydraulic power steering	■
Outboard planetary axles	■
Fixed front axle	■
Oscillating rear axle	■
Parking brake, spring-applied hydraulic release	■
Sealed, self-adjusting brakes	■
Tires, 20.5R25 L3 radial standard	■
Outboard brakes	■

## Other

Centralized lubrication	–
Air compressor	●
Handrails, entrance & service steps	■
Handrails, roof-mounted	●
Roof cover	●
Skid-resistant entrance steps	■
Skid-resistant service platforms	■
Drawbar & pin	■
Wheel chocks	■
Rear fender, full	●
Additional counterweight	●
Manuals	■
- Operation & Maintenance	■
- Parts	■
- AEM Safety Manual	■
DEVELON Fleet Management	■
Vandalism protection	■
- Lockable panels	■
- Lockable fluid fill points	■
- Anti-theft protection (password)	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual DEVELON equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of DEVELON units may show other than standard equipment.

# Powered by Innovation

# DEVELON

A brand of HD Hyundai Infracore.

[na.develon-ce.com/dl250tc-7](http://na.develon-ce.com/dl250tc-7)

DL250TC-7 Wheel Loader Spec Sheet  
Printed in the U.S.A.  
23906\_003\_D092123

©2023 HD Hyundai Infracore. All rights reserved.